LVT Sp. z o.o.



Midas 22W IP65 4000K IK10 LED Ceiling Light for Hallways

SKU: **0737**

EAN: **5908263380455**

Cechy produktu

Cecha	Wartość
Light source	LED SMD
Certificates	CE
Color of Light	4,000 K
Useful luminous flux (ϕuse 360°)	2200 lm
Brightness in standby mode	20%
Color rendering index	RA>80
Beam angle	120°
Power	22 W
Sensor transmission power	<0.2 mW
PF	>0.9
Input voltage	AC 220-240 V 50/60 Hz
Standby Power Consumption	<0.5 W
Control Method	4 adjustable knobs
Dimming	No
Motion Detection	0.6–1.5 m/s
Detection Details	2–8 m (ceiling); 5–15 m (wall) [adjustable]

Cecha	Wartość
Detection angle	180° / 360°
Detection distance	15 m
Motion sensor	Microwave corridor
Activation threshold	<3–2,000 LUX
Frequency	5.8 GHz CW radar, ISM band
Material	PC
Resistance Class	IP65
IK rating	IK10
Service life	50,000 hours
Number of on/off cycles	50000x
Operating temperature	-15 to 35 °C
Operating time	10±3 s / 12±1 min
Standby Time	0s / 90s / 5min / 10min / 30min / +∞
Start-up time	<0,1s
Warranty	3–5 years
Additional Information	2 brightness modes: 2,200 lm (100%) / 400 lm (standby 20%)
Installation Height	2–4 m (ceiling) / 1.5–3.5 m (wall)
Dimensions	Ø300 x 40 mm
Master carton packaging	10 pcs (11.30 kg)
Quantity per package	10 pcs (10.40 kg)
Quantity per pallet	250 pcs (275.00 kg)