LVT Sp. z o.o.



Tiga2 50W 4500K Black SMD LED Floodlight with PIR Sensor

SKU: **1225**

EAN: **5904703028321**

Cechy produktu

Cecha	Wartość
Diode type	SMD 2835
Light source	LED SMD
Color of Light	4,500 K
Luminous flux	4000 lm
Useful luminous flux (ϕuse 360°)	5400 lm
Luminous efficacy	80 lm/W
Color rendering index	RA>80
Beam angle	120°
Power	50 W
PF	>0.9
Input voltage	AC 180-240 V 50/60 Hz
Current consumption	0.45 W (operating) 0.1 W (idle)
Detection Details	2–8 m [<24 °C] (adjustable)
Detection angle	120°
Detection distance	8 m
Motion sensor	PIR

Cecha	Wartość
Activation threshold	<10–2,000 LUX
Material	Aluminum + Tempered Glass
Resistance Class	IP65
Electrical Protection Class	I
Service life	30,000 hours
Number of on/off cycles	15000x
Operating temperature	-20 to 40 °C
Operating Humidity	<93% RH
Lighting Duration	5±2 s - 8±3 min
Start-up time	<0,1s
Installation Height	1.8–2.5 m
Power cord length	30cm
Dimensions	151 x 50 x 200 mm
Dimensions of the floodlight	151 x 23 x 123 mm
Master carton packaging	20 pcs
Quantity per package	30 pcs
Quantity per pallet	600 units