LVT Sp. z o.o.



Microwave LSp High Bay Module

SKU: **4354**

EAN: **5904703000969**

Cechy produktu

Cecha	Wartość
Brightness in standby mode	10% / 20% / 30% / 50%
Sensor transmission power	<0.5 mW
Input voltage	AC 120-277 V AC 50/60 Hz
Current consumption	1.5 W
Standby Power Consumption	<0.5 W
Control Method	Remote Control 4343 (not included) Works with all LSp High Bay models
Motion Detection	0.6–1.5 m/s
Detection angle	360°
Detection sensitivity	25% / 50% / 75% / 100%
Motion sensor	Microwave corridor
Activation threshold	5 / 15 / 30 / 50 / 100 / 150 LUX
Frequency	5.8 GHz CW radar, ISM band
Material	ABS
Resistance Class	IP65
Operating temperature	-35 to 55 °C

Cecha	Wartość
Operating time	5 seconds / 30 seconds / 1 minute / 3 minutes / 10 minutes / 20 minutes / 30 minutes
Standby Time	0s / 10s / 1 min / 3 min / 5 min / 10 min / 30 min / +∞
Installation Height	Max. 15 m
Module Dimensions	50 x 34 mm
Master carton packaging	10 pcs
Quantity per package	50 pcs
Quantity per pallet	-