LVT Sp. z o.o.



Milight LED Panel 12W RGB+CCT MLT066

SKU: **MLT066**

EAN: **5904703004363**

Cechy produktu

Cecha	Wartość
Diode type	SMD LED
Features	RGB+CCT color changing, dimming, auto-transmission, and auto-synchronization (control of an unlimited number of controllers with a single remote), 9 dynamic lighting modes
Color of Light	RGB + 2700-6500 K
Luminous flux	1056 lm
Color rendering index	RA>80
Beam angle	120°
Power	12 W
Transmission power	6 dBm
Input voltage	AC 100-240 V 50/60 Hz
Radio Communication	2.4 GHz RF (requires a Milight remote control), Wi-Fi (requires a WL-BOX1 gateway)
Material	Aluminum + PC
Resistance Class	IP20
Service life	50,000 hours

Cecha	Wartość
Number of on/off cycles	20000x
Operating temperature	-20 to 60 °C
Compatibility	FUT089, FUT088, FUT092, MLT092, FUT096, MLT096, FUT087, MLT087, FUT006, FUT007, B8, B0, B3, B4, B2, B1, WL-Box1
Range	30 m
Mounting hole	Ø145–150 mm
Dimensions	Ø180 x 40 mm
Master carton packaging	20 pcs
Quantity per package	40 pcs